



Description

Appin is a low variation light beige limestone. Displaying a subtle abundance of fossils, its tumbled edge assist in making it suit scenarios where a rustic feel is required, but its colour makes this a popular choice for contemporary situations also. This is available in a tile or paver format and is a great choice for both interior and exterior flooring.

Available Formats & Finishes

Drop edge



610x406x30/60mm

Tile



610x406x15mm

French Pattern



1 = 200x200mm (2pc)
 2 = 400x200mm (1pc)
 3 = 400x400mm (2pc)
 4 = 600x400mm (1pc)
 1 pack = 0.72 m² / Pattern

Bullnose



610x406x30/60mm

Paver



610x406x30mm




Product Technical Data Sheet

	Finish	Dimension	Length & height Variation	Thickness Variation	Weight Approx.
Tile/Paver	Sandblasted & Tumbled	600x400x15mm	+/- 5mm	+/- 2mm	35kg/m ²
Tile/Paver	Sandblasted & Tumbled	600x400x30mm	+/- 5mm	+/- 2mm	70kg/m ²
French Pattern	Sandblasted & Tumbled	15mm	+/- 5mm	+/- 2mm	35kg/m ²
French Pattern	Sandblasted & Tumbled	30mm	+/- 5mm	+/- 2mm	70kg/m ²
Treads	Sandblasted & Tumbled with Bullnose	600x400x30mm	+/- 5mm	+/- 2mm	18kg each
Treads	Sandblasted & Tumbled with Drop Edge	600x400x30/60mm	+/- 5mm	+/- 2mm	20kg each
Tile/Paver	Acid Washed & Tumbled	600x400x15mm	+/- 5mm	+/- 2mm	35kg/m ²
Tile/Paver	Acid Washed & Tumbled	600x400x30mm	+/- 5mm	+/- 2mm	70kg/m ²
French Pattern	Acid Washed & Tumbled	15mm	+/- 5mm	+/- 2mm	35kg/m ²
French Pattern	Acid Washed & Tumbled	30mm	+/- 5mm	+/- 2mm	70kg/m ²
Treads	Acid Washed & Tumbled with Bullnose	600x400x30mm	+/- 5mm	+/- 2mm	18kg each
Treads	Acid Washed & Tumbled with Drop Edge	600x400x30/60mm	+/- 5mm	+/- 2mm	20kg each

SLIP RATING

Sandblasted & Tumbled	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	66	62	58	60	58
Reported SRV of Sample:	61				
Class:	P5				
Acid Washed & Tumbled	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	44	42	36	36	39
Reported SRV of Sample:	39				
Class:	P3				

Characteristics

		
Stone Texture Grades	Stone Texture Grades	Stone Texture Grades
M	P5/P3	Medium (VM)

At Aussietecture, quality control isn't an afterthought—it's built into every step of the process. We don't wait until the stone is cut to inspect it; instead, we start from the very beginning of production. By applying rigorous, proactive quality standards at every stage, we ensure that excellence is not just achieved—it's guaranteed. Every cut, every detail, every step is monitored with 110% dedication to quality.



The advantages of most Aqua Mix® Stone, Tile & Grout Sealers are: They're safe water-based products that are utilizing the latest in sealer technology. Most emit low or no VOCs (Volatile Organic Compounds), and prevent a variety of stains – both oil and water-based. Allow MVT (Moisture Vapour Transmission)

Recommended Sealing Solutions

Desired Effect	Recommended Product	Result
Natural Look and Stain Protection	Sealer's Choice Gold	Provides maximum stain protection with a 4-hour cure time while maintaining a natural look. Utilizes safe, non-toxic water-based technology.

Approx. Coverage m² per/L

	Textured
Limestone	6-10m ²