

BINDOON

LIMESTONE



Description

Bindoon Limestone is a popular choice for hotel lobbies, facades, restaurant floors, and public areas globally. The colour of Bindoon is black-gray background adorned with white veins. These delicate veins contrast subtly with the dark grey backdrop, imbuing the stone with visual depth and interest. The addition of white veining brings an air of elegance and timeless beauty, enriching the aesthetic appeal of any indoor and outdoor space.


Available Formats & Finishes

Drop edge



600x400x30/60mm

Tile



600x400x12mm

Bullnose




600x400x30/60mm

Paver



600x400x30mm

French Pattern



1 = 200x200mm (2pc)
2 = 400x200mm (1pc)
3 = 400x400mm (2pc)
4 = 600x400mm (1pc)
1 pack = 0.72 m² / Pattern

Cobblestone



90x90x30mm




Product Technical Data Sheet

	Finish	Dimension	Length & height Variation	Thickness Variation	Weight Approx.
Tile/Paver	Tumbled	600x400x12mm	+/- 5mm	+/- 2mm	28kg/m ²
Tile/Paver	Tumbled	600x400x30mm	+/- 5mm	+/- 2mm	70kg/m ²
French Pattern	Tumbled	12mm	+/- 5mm	+/- 2mm	28kg/m ²
French Pattern	Tumbled	30mm	+/- 5mm	+/- 2mm	70kg/m ²
Treads	Tumbled with Bullnose	600x400x30mm	+/- 5mm	+/- 2mm	18kg each
Treads	Tumbled with Drop Edge	600x400x30/60mm	+/- 5mm	+/- 2mm	20kg each
Cobblestone	Tumbled	90x90x30mm	+/- 5mm	+/- 2mm	65kg/m ²
Tile/Paver	Antique	600x400x12mm	+/- 5mm	+/- 2mm	28kg/m ²
Tile/Paver	Antique	600x400x30mm	+/- 5mm	+/- 2mm	70kg/m ²
French Pattern	Antique	12mm	+/- 5mm	+/- 2mm	28kg/m ²
French Pattern	Antique	30mm	+/- 5mm	+/- 2mm	70kg/m ²
Treads	Antique with Bullnose	600x400x30mm	+/- 5mm	+/- 2mm	18kg each
Treads	Antique with Drop Edge	600x400x30/60mm	+/- 5mm	+/- 2mm	20kg each
Cobblestone	Antique	90x90x30mm	+/- 5mm	+/- 2mm	65kg/m ²

SLIP RATING

Tumbled	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	39	41	39	35	40
Reported SRV of Sample:	39				
Class:	P3				
Antique	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	49	48	49	49	49
Reported SRV of Sample:	49				
Class:	P4				

Characteristics

 <p>Stone Texture Grades</p> <p>M</p>	 <p>Stone Texture Grades</p> <p>P3/P4</p>	 <p>Stone Texture Grades</p> <p>High (VH)</p>
---	---	---

At Aussietecture, quality control isn't an afterthought—it's built into every step of the process. We don't wait until the stone is cut to inspect it; instead, we start from the very beginning of production. By applying rigorous, proactive quality standards at every stage, we ensure that excellence is not just achieved—it's guaranteed. Every cut, every detail, every step is monitored with 110% dedication to quality.



The advantages of most Aqua Mix® Stone, Tile & Grout Sealers are: They're safe water-based products that are utilizing the latest in sealer technology. Most emit low or no VOCs (Volatile Organic Compounds), and prevent a variety of stains – both oil and water-based. Allow MVT (Moisture Vapour Transmission)

Recommended Sealing Solutions

Desired Effect	Recommended Product	Result
Natural Look and Stain Protection	Sealer's Choice Gold	Provides maximum stain protection with a 4-hour cure time while maintaining a natural look. Utilizes safe, non-toxic water-based technology.

Approx. Coverage m² per/L

	Textured
Limestone	6-10m ²